

目录

目录	1
公共错误码	2

公共错误码

调用接口失败，不会返回结果数据；HTTP请求返回一个4xx或5xx的HTTP状态码，返回的HTTP消息体中包含具体的错误代码(code)及错误信息(message)；与调用成功一样还包含请求ID(RequestId)，在调用方找不到错误原因时，可以联系金山云客服，并提供RequestId，以便我们尽快帮您解决问题。

错误代码(Code)	错误消息(Message)	HTTP 状态码	中文描述(语义)
IncompleteSignature	Date must be in ISO-8601 'basic format'. Got '%s'. See http://en.wikipedia.org/wiki/ISO_8601 .	400	Date必须符合ISO_8601基本格式，参考： http://en.wikipedia.org/wiki/ISO_8601
IncompleteSignature	KSC query-string parameters must include %s. Re-examine the query-string parameters.	400	查询条件中缺少签署信息，查询条件中必须包含" X-Amz-Algorithm "、“ X-Amz-Credential “、“ X-Amz-SignedHeaders “、“ X-Amz-Date “信息
IncompleteSignature	Unsupported ksc 'algorithm': %s.	400	只支持如下签名算法：AWS4-HMAC-SHA256
IncompleteSignature	Authorization header requires 'Credential' parameter. Authorization=%s.	400	请求Authorization header中需要包含“Credential”参数
IncompleteSignature	Credential must have exactly 5 slash-delimited elements, e.g. accesskeyid/date/region/service/aws4_request, got: %s.	400	请求Authorization header中中“Credential”至少包含5项以斜杠分隔的元素，如：keyid/date/region/service/aws4_request
IncompleteSignature	Authorization header format error.	400	请求Authorization header的格式错误
IncompleteSignature	Authorization header requires existence of either a 'X-Amz-Date' or a 'Date' header, Authorization=%s	400	请求中缺少“X-Amz-Date”或者“Date” header信息
IncompleteSignature	Authorization header requires 'Signature' parameter. Authorization=%s	400	请求Authorization header中缺少“Signature”信息
IncompleteSignature	Authorization header requires 'SignedHeaders' parameter. Authorization=%s	400	请求Authorization header中缺少“SignedHeaders”信息
MissingTimestamp	The request is missing timestamp parameter.	400	请求无合法timestamp，请检查请求
InvalidParameterValue	An invalid or out-of-range value was supplied for the input parameter %s.	400	输入参数%s的值无效、不合法或者超出范围
InvalidMethod	The method %s for is not valid for this web service.	400	Method %s对当前web服务无效
MissingParameter	An value must be supplied for the input parameter %s.	400	输入参数 %s的值不能为空
InvalidQueryParameter	The query parameter %s is malformed or does not adhere to KSC standards.	400	查询参数 %s格式不对、不存在或者不符合金山云标准
MissingSignature	The Request is missing Signature Parameter.	400	请求被拒绝，因为没有合法的签名
InvalidActionOrVersion	The action %s or version %s is not valid for this web service	400	action %s 或 version %s不合法
InvalidTimestamp	Invalid Timestamp(%s). Pls in 15mins	400	请求时间戳不合法(%s)，请保持请求时间戳在15分钟以内
MissingAccesskey	Access Key is Missing	400	请求被拒绝，因为没有秘钥
InvalidAccesskey	Invalid Accesskey(%s)	400	非法秘钥(%s)
SignatureNotMatch	The Signature is not matched	400	签名不匹配，请检查签名算法
UnavailableRegion	The region %s is unavailable for the openapi	400	此openapi不具备%s区域的服务
MissingAuthenticationToken	Request is missing 'Host' header.	403	请求header中缺少Host
MissingAuthenticationToken	Request is missing Authentication Token.	403	请求header中缺少认证token

MissingAuthenticationToken	%s not in Http Header.	403	%s不在Http header中
SignatureDoesNotMatch	Host' must be a 'SignedHeader' in the Authorization.	403	请求的SignedHeader中必须包含Host
SignatureDoesNotMatch	Credential should be scoped with a valid terminator: 'aws4_request', not: %s.	403	请求Authorization header中的“Credential”末尾必须是“aws4_request”
SignatureDoesNotMatch	Credential should be scoped to a valid region, not:%s.	403	请求Authorization header中的“Credential”中的Region信息无效
SignatureDoesNotMatch	Credential should be scoped to correct service: %s.	403	请求Authorization header中的“Credential”中的Service信息无效
SignatureDoesNotMatch	The request signature we calculated does not match the signature you provided.	403	请求中提供的签名与实际计算结果不匹配
SignatureDoesNotMatch	Signature expired:%s.	403	签名已过期
SignatureDoesNotMatch	Date in Credential scope does not match YYYYMMDD from ISO-8601 version of date from HTTP.	403	请求Authorization header中的“Credential”中的Date应该是ISO8601基本格式，形如“YYYYMMDD”
InvalidClientTokenId	The security token included in the request is invalid.	403	请求中提供的AccessKeyId无效
InvalidAuthenticationCode	Request was rejected because of lack of policy.	403	该用户调用权限不足，请查询用户相关权限
InvalidAuthenticationCode	lack of policy to [%s] the resources[%s]	403	该用户调用权限不足，缺少操作%s资源%s的权限
InvalidAuthenticationCode	the policy deny to [%s] the resources[%s]	403	权限拒绝操作%s资源%s的行为
ServiceUnavailable	Request was rejected because it referenced an 'InnerApi' that does not have an internal service	404	请求被拒绝，因其引用的InnerAPI无内部服务。
NoSuchEntity	Request was rejected because it referenced an 'InnerApi' that does not exist.	404	请求被拒绝，因其引用的InnerAPI不存在
ServiceUnavailable	Invalid service(%s)	404	请求被拒绝，因其引用的服务(%s)不存在
LimitExceeded	Request was rejected because the request speed of this openAPI is beyond the current flow control limit.	409	请求被拒绝，因该openAPI接口访问速度已达到流控上限
FlowLimitExceeded	Request was rejected because the request speed of this openAPI is beyond the current flow control limit.	409	请求被拒绝，因openapi接口访问速度已达到流控上限
DryRunOperation	Request would have succeeded, but DryRun flag is set	412	请求本可成功，但由于设置DryRun标记未成功
ServiceUnavailable	Exception %s	500	服务暂不可用
ServiceUnavailable	Auth Service is unavailable because of an unknown error, exception or failure	500	验签或授权服务暂不可用
ServiceUnavailable	OpenAPI or Service is unavailable because of an unknown error, exception or failure.	500	openAPI或服务暂不可用。
ServiceTimeout	Internal Service is unavailable because of time out.	500	内部服务异常或超时暂不可用。